

DDS 500A – Insulating Glass Products

Dlubak offers a line of insulating glass products for architectural, ballistic, security and heavy glass applications. Assembled as a dual sealed unit, Dlubak insulating glass /enviro-pane is available as two or more lites separated by an air or gas filled space.

Glass	All types of glass including clear and tinted float glass, coated and uncoated, pattern and specialty glass (upon review). Heat-treated and/ or laminated glass may be incorporated in the assembly. Refer to our appropriate Data Sheet for limitations.			
	Annealed	Heat-treated	Screen-printed	Spandrel
Maximum Size	90" x 137"	84" x 137"	80" x 130"	73" x 120"
Minimum Size	8" x 18"	12" x 12"	N/A	N/A
Minimum Glass Thickness	3/16" spacer plus glass.	12" x 12"	N/A	N/A
Maximum Overall Thickness	2 1/2"	2 1/2"	N/A	N/A
Certification	Dlubak insulating glass units are rated with the Insulating Glass Certification Council (IGCC) in accordance with ASTM Specification E 2190. Ancillary processes meet the following specifications when applicable. ASTM C-1036 Flat Glass, ASTM C-1048 Heat Treated Flat Glass H/S and F/T ASTM C-1172. ANSI Z97.1 and CPSC 16 CFR 1201, CAT.I and II.			
Warranty	The products of Dlubak Corporation carry limited warranties of varying duration. Contact our Customer Service Department for detailed information for your project.			
Samples	Project samples are available at no charge in conjunction with bonafide quote requests. Standard size is 12" X 12". Prototypical sizes are available at a nominal cost.			